

Beetle Kill Pine Architectural & Design Specifications

MINIMUM ORDER	200 square feet
SURFACES	Floors, walls & ceilings
SPECIES	Salvaged Montana Beetle Kill Ponderosa Pine
GRADE QUALITY	99% usable
STABILITY	Fine grain averaging 15 growth rings per inch
HARDNESS	510 Janka Rating
MOISTURE CONTENT	Cured & kiln dried to 6-8% moisture content
THICKNESS	Full 3/4"
WIDTHS	5 1/4" & 7" face coverage
LENGTH	Random lengths up to 8'
GRAIN	Mixed
PROFILE	Micro bevel edges, relief kerfs, clinch line, T&G and end-matched (T&G on the ends)
FINISH	Available unfinished T&G , prefinished T&G wall paneling, prefinished Skiplap Wall Cladding, or prefinished T&G flooring
CERTIFICATION	100% salvaged timber harvested within 100 mile radius of our facility. LEED eligible based on various criteria including salvaged and locally sourced material.
DISTRIBUTION	Factory direct shipping anywhere in the U.S.
DISCLAIMER	This is a natural wood product. Color, texture, grain, and sheen will vary from board to board.
PRICING	Call or email square footage and zip code for a delivered price to your project. 406.642.7120 or www.sustainablelumberco.com/contact