Wall and Ceiling Boards Architectural & Design Specifications

- MADE IN THE USA
- MINIMUM ORDER – 200 sq.ft.
- SURFACES – walls & ceilings
- SPECIES – Salvaged and sustainably certified Douglas Fir
- GRADE QUALITY – 99% usable
- STABILITY – Fine grain averaging 15 growth rings per inch
- HARDNESS – 770 Janka Rating
- MOISTURE CONTENT – Cured & kiln dried to 6-8% moisture content
- THICKNESS – Full 3/4″
- WIDTHS – 5 1/8″, & 7″ face coverage
- LENGTH – Random up to 8′
- GRAIN – Mixed
- COLOR – 5 prefinished colors
- TEXTURE – Wire Brushed and lightly sanded
- PROFILE – Micro bevel edges, relief kerfs, clinch line, T&G, and end-matched (T&G on the ends)
- FINISH – Multi-step factory finish including hand-rubbed penetrating oils & 2 coats of a clear satin varnish
- CERTIFICATION – 100% salvaged or SFI Certified wood harvested within a 100-mile radius of our facility. LEED eligible based on various criteria including salvaged and locally sourced material
- DISTRIBUTION – Factory direct shipping anywhere in the U.S.
- DISCLAIMER – This is a natural wood product. Color, texture, grain, and sheen will vary from board to board.
- PRICING - Call or email square footage and zip code for best delivered price to your project. 406.642.7120 or info@sustainablelumberco.com